

Ergonomically styled small size stroboscope with one hand operation and maximum performance Art.No.:3118

An.No..5110

Very compact, ergonomically styled, processor-controlled ministroboscope with analogue dial and external powerpack operation. (powerpack 2020.03 optional)

Features:

Small dimensions, low weight, innovative and elegant design, trouble-free processortechnology, very precise adjustment of the flash frequency by rotary knop scale, stabilized voltage, temperature constant.

General Data: Light Source: Flash bulb: Light intensity: Flash duration: Frequency range:

Trigger action: - Internal control: Display:

Accuracy: Flash power control:

Technical Data: Power supply:

Housing:

Dimensions: Weight:

Mob.: +91 99699 28644

flash bulb, internal socket-mounted Xenon-longlife max. 450 Lux in 50cm distance from reflector (beam axis) approx. 2 - 7 μ s 2,5 - 300Hz = 150 - 18.000 RPM (min-1) subdivided into 2 overlapping ranges 1.) 2,5 - 66,6 Hz = 150 - 4000 RPM (min-1) 2.) 61,6 - 300 Hz = 3700 - 18000 RPM (min-1) internal oscillator by dial potentiometer reading in Hz (flashes per sec.) or RPM (min-1) by parallax-free scale setting. \pm 2% of the set value

by change of frequency range via control push button

Fax:+91-22-28700015

12V DC Power consumption: max. 1,7A Ergonomically styled industrial design, shatterproof plastic, VDE-approved $155 \times 95 \times 85$ mm ca. 0,450 kg

www.stroboscope.ii

MOVISTROB® Type 3000 B/A



Accessories:

Accupack Type 2020.03 Red Filter Type 2000.11 Protective Spectacles incl. case Type 950.01 Telescopic Tripod Type 950.00 Carrying Case Type 3000.10 Spare flash bulbs

Notice:

Recommended accessory: Power Pack Type 2020.03 If the powerpack type 2020.03 is not required we enclose a special battery cable with clamp coupling free of charge.

